

TWO POST LIFT FLOOR PLATE



SPECIFICATIONS:

- Structure : Two post lift with floor plate
- Capacity(kg) : 3500
- Lift height(mm) : 1800
- Rise time(s) : 50
- Drop time(s) : 20
- Power of motor (kw) : 2.2
- Power supply(v) : 380/220
- Machine Height(mm) : 2826
- Machine Width(mm) : 3200
- Frame Width(mm) : 3420

FEATURES :

- 5mm "international standard" column steel plates
- 8mm brace arm and 6mm Internal sliding column
- Wearable, Anti-High temperature, high strength oiliness macromolecule nylon slide block
- Require no less than 150mm cement on the ground, At least C25
- Double safe Antiskid device, from Column ladder safe to close protection by dynamic hydraulic pressure, Ensure double safe stay for vehicle
- Double safe Antiskid device, from Column ladder safe to close protection by dynamic hydraulic pressure, Ensure double safe stay for vehicle
- Endure Max 5 T destructive testing , fulfill 3.5T/4T actual working conditions
- Chain style pulling device , make the security parameter up to 5 times
- Total Mold tooling technology, to ensure the conformity of both many a holes and welding places
- Digital control raw materials processing center ensure the discrepancies at % stage & product consistency
- Double cylinder dynamic hoist drive device, capacity is more than 3.5T/4T
- Aluminum pump device , running time without any break down for at least 40,000 H
- Mechanical control hydraulic pressure configuration. Simple, endurable and reliable